

PREISE - PRICES

DURCHMESSER LUFTSTRÖMUNG DIAMETER AIR PASSAGE	L →	LUFTDÄMPFUNG BEI 250 Hz ATTENUATION AT 250 HZ	
Ø mm	mm	dB(A)	€
80	500	9,5	43,98
100	500	8	47,96
125	500	6,5	55,68
140	500	5,5	59,65
150	500	5	61,34
160	500	5	62,18
180	500	4,5	75,68
200	500	4,5	76,89
224	500	4,5	92,07
250	500	4	101,23
280	500	3,5	112,68
300	500	3	117,61
315	500	3	120,88
355	500	3	150,17
400	500	2,5	181,13
80	1000	19	67,96
100	1000	16	78,21
125	1000	13	88,82
140	1000	11	102,79
150	1000	10	102,79
160	1000	10	102,79
180	1000	9	125,44
200	1000	9	125,44
224	1000	9	148,47
250	1000	8	148,47
280	1000	7	171,12
300	1000	6	171,12
315	1000	6	174,87
355	1000	6	194,02
400	1000	5	212,10
80	1500	28,5	84,96
100	1500	24	95,93
125	1500	19,5	108,83
140	1500	16,5	121,11
150	1500	15	123,04
160	1500	15	123,52
180	1500	13,5	144,61
200	1500	13,5	152,33
224	1500	13,5	178,60
250	1500	12	194,02
280	1500	10,5	231,86
300	1500	9	237,76
315	1500	9	238,49
355	1500	9	286,70
400	1500	7,5	341,53
80	2000	39	109,78
100	2000	32	125,93
125	2000	26	133,41
140	2000	22	155,46
150	2000	20	157,99
160	2000	20	158,70
180	2000	18	182,57
200	2000	18	194,86
224	2000	18	225,71
250	2000	16	243,55
280	2000	14	291,40
300	2000	12	298,02
315	2000	12	338,40
355	2000	12	383,58
400	2000	10	446,25



MERKMALE:

Beweglicher Schalldämpfer für runde Kanäle, Isolierung 50 mm.

AUSFÜHRUNG:

Außenblech aus Aluminium mit Schallsisolierung aus Mineralwolle und Innenblech aus Aluminium. Nicht entflammbar nach DIN 4102 Kl. 1, resistent bis 200 °C, Krümmungsradius gleich dem 3-fachen des Durchmessers.

BEFESTIGUNG:

Anschluss steckbar.

CHARACTERISTICS:

Flexible circular sound attenuators, insulation 50 mm.

CONSTRUCTION:

External sheet of aluminium with mineral wool insulation and inner sheet of aluminium. Not flammable in accordance with DIN 4102 class A1, resistant to 200 °C, bending radius equal to 3 diameters.

FIXING:

Coupling.

ZEICHNUNGEN - DRAWINGS

